

Specifications

WEIGHT <ul style="list-style-type: none"> 1.5 lbs - 1.75 lbs / square foot (depending on design) 	MOISTURE RESISTANCE <ul style="list-style-type: none"> Exceptional humidity and moisture resistance
FIRE RATING <ul style="list-style-type: none"> ASTM E84 surface burning characteristics Class A Fire and smoke proof 	COMPOSITION <ul style="list-style-type: none"> Light weight gypsum Proprietary and patented formulation
LIGHT REFLECTANCE <ul style="list-style-type: none"> High light reflectancy 	DIMENSIONS <ul style="list-style-type: none"> 23 5/8" x 23 5/8" x 1/2"
ACOUSTICAL PROPERTIES <ul style="list-style-type: none"> ASTM E1050 sound absorption measurements Noise reduction coefficient 0.43 - 0.50 	COLOR <ul style="list-style-type: none"> White factory applied vinyl acrylic latex Custom colors and finishes available
GREEN PRODUCT <ul style="list-style-type: none"> Recyclable Non-toxic 	ENVIRONMENTALLY SAFE <ul style="list-style-type: none"> Recyclable Non-toxic

Applications

Retail Stores, Casino, Hotels, Executive Suites, Conference Rooms, Custom Homes, Theatres, Religions Places of Worship, Government Buildings, Court Rooms, Clean Rooms, Retrofit.

Special Features

- Drills or cuts easily for installation of down lights, sprinklers and vents
- The consistent thickness, weight and detail of our tiles produce a uniformity that ensures stability in design
- The lightweight composition of our ceiling tiles results in no excess weight and no excess stress on the structure
- Our ceiling tiles maintain size and plane (no warping)

DEALERS / DISTRIBUTORS

LIGHTWEIGHT GYPSUM CEILING TILES

MANUFACTURED BY



173 Adesso Drive, Unit 2, Concord, Ontario, Canada L4K 3C3
Tel, 905-738-8089 Fax, 905-760-9234
www.castleaccesspanels.com
























Applications:
Ideal for environments requiring rich, elegant, dramatic ceilings.

Features:
Lightweight design for ease of handling and cutting.
Factory cutouts available for light fixtures, speakers, etc.
Open Cell coffer (accepts acoustical insert).
No hold down clips required.
Washable and portable.
Optional factory applied paints and stains.

Benefits:
Extraordinary aesthetic appeal.
Ease of cutting reduces installation cost versus competitive panels.
Dimensionally stable. Will not warp, sag or shrink.
Contains 70% post consumer recycled glass.
100% recyclable at end of useful life.
May support eligibility for USGBC LEED Certification Credit.


LAY - IN GRG 2x2 COFFERED AND FLAT CEILING PANELS

 LC-050 FIELD TILE WITH REVEAL	 LC-070 FIELD TILE WITHOUT REVEAL	 LC-100 LINEAR TUSCAN	 LC-120 CLASSIC LINEAR	 LC-130 CLASSIC PEARL	 LC-140 GIORGIO	 LC-200 EGG AND DART
 LC-300 DENTIL	 LC-400 ACANTHUS LEAF	 LC-410 CLOVER FRET	 LC-500 MODERN SPHERES	 LC-510 DECO SHAPES	 LC-520 RADIANT	 LC-530 LAMBS TOUNGE + PANEL
 LC-540 LAMBS TOUNGE	 LC-550 ROSETTE	 LC-600 AMOUR	 LC-610 BLAKE	 LC-620 LATTICE	 LC-650 (30" ONLY) LA CRÈME	 LC-900 LINEAR TUSCAN WITH 9" ACCESS DOOR

OPEN CELL - ACOUSTICAL GRG COFFERED CEILING PANELS WITH OPTIONAL INSERT





PANEL A	INSERT B
24"	19 1/8"
36"	31 1/8"
48"	43 1/8"

FINISHES

										
STANDARD FACTORY WHITE	CC-40 IVORY PATINA ANTIQUE & GLAZE	WOOD GRAIN MAHOGANY	WOOD GRAIN PEARL OAK	WOOD GRAIN NATURAL OAK	WOOD GRAIN MEDIUM WALNUT	METALLIC BRASS	METALLIC BRONZE	METALLIC COPPER	METALLIC IRON	METALLIC PEWTER

* ALL TILES TO BE ORDERED IN FULL CARTONS ONLY